

VANJAX SALES PVT. LTD.,

an ISO 9001:2008 COMPANY



VANJAX SELF PROPELLED SCISSOR LIFT BATTERY OPERATED

MODEL-VXLTM		320/10 SPDCVX	320/12 SPDCVX	320/13.8 SPDCVX	200/15.7 SPDCVX	FEATURES
S.W.L	kg	320	320	320	200	
S.W.L on extn	kg	113	113	113	113	PROPORTIONAL CONTROLS
No of persons Max	no	2	2	2	2	AUTOMATIC POT HOLE PROTECTION
Working ht	mtr	10	12	13.8	15.7	SELF LOCK GATE ON PLATFORM
Platform Ht	mtr	8	10	11.8	13.7	DRIVABLE AT FULL HEIGHT
Overall length	mtr	2.48	2.48	2.48	2.84	2 WD
Overall width	mtr	1.19	1.19	1.19	1.25	AUTOMATIC BRAKES
Overall ht (rails up)	mtr	2.32	2.44	2.62	2.62	EMERGENCY LOWERINIG SYSTEM
Ovarall ht (rails downn)	mtr	1.78	1.92	2.09	2.09	TILT SENSOR WITH ALARM
Platform size	mtr	2.27X1.12	2.27X1.12	2.27X1.12	2.64 X 1.12	HORN
Platform Extn	mtr	0.9	0.9	0.9	0.9	HOURL METER
Ground clearance	mtr	0.1/0.019	0.1/0.019	0.1/0.019	0.1/0.019	SAFETY POCKETS
Wheel base	mtr	1.87	1.87	1.87	2.22	FOLDING GAURDRAILS
Turning radius (inside)	mtr	0	0	0	0	EXTENDED PLATFORM
Turning radius(outside)	mtr	2.2	2.2	2.2	2.65	CHARGER PROTECTION
Drive motors		24/1.5	24/1.5	24/1.5	24/1.5	FLASHING BEACON
Lifting motors	v/kw	24/4.5	24/4.5	24/ 4.5	24/4.5	OPTIONALS
Travel speed(stowed)	km/hr	4	4	4	4	AC POWER POINT
Travel speed(raised)	km/hr	0.8	0.8	0.8	0.8	AIR LINE
MAX DRIVABLE HT	mtr	FULL	FULL	FULL	FULL	BELLOWS / MESH GUARD
Up/Down Speed	sec	40/30	58/48	65/45	75/65	JACKING MECH FOR SAFETY
Batteries	v/ah	6X4X225	6X4X225	6 x4 x 225	6 x4 x 225	OVERLOAD SENSOR WITH ALARM
Integrated charger	v/a	24/25	24/25	24 /25	24/25	
Gradeability	%	25	25	25	25	
Tyres solid rubber DIAXTHK	mm	381X127	381X127	381X127	381X127	
Weight	kg	2665	2760	2950	3400	

Regd. Off. Unit-1 (VXC-1)
343, Sidco Industrial Estate
Ambattur
Chennai 600098, T.N., India

Phone : 044 - 4282 1000
2625 5300
2625 4875
Fax : 0091-44-4598 5700

e-Mail : info@vanjax.com
jfk@vanjax.com
gmsales@vanjax.com
website : www.vanjax.in

Vanjax Factory Unit-2 (VXC-2)
S.No.230/11, Mevalur Kuppan
Sriperumbudur
Chennai 602105, T.N., India

HYDRAULIC POWER IN ACTION ★ YOU NEED IT, VANJAX MAKES IT.